



05000ST Motor Oil 5W-30 Premium Synthetic ST

Dokumentversion: 15 apr. 2024



beskrivning

This Premium Synthetic 'Mid SAPS ' engine oil is designed for gasoline and diesel engines equipped with an exhaust after-treatment system. This special formulation complies to the Stellantis FWP9.55535/03 specification which is mandatory for DV5R engines until OPR 16885. These D5VR engines are used in Citroën, DS, Peugeot, Fiat, Toyota, Opel and Vauxhall. The optimized cleanliness, reduces wear increases the lifetime of the mechanical components and the engine. This engine oil is also suitable for engines requiring PSA B71 2290 specification with viscosity grade 5W-30.

Användningshandbok

Enligt specifikationerna för

ACEA C3
API SN Plus
PSA B71 2290
Stellantis FPW9.55535/03

Förpackningsenheter

ARTIKELNR.	VOLYM	ANTAL PER ENHET	ANTAL PER PALL
05001ST	1 L	6	450
05005ST	5 L	4	112
05020ST	20 L	1	30
05060ST	60 L	1	6
05205ST	205 L	1	2
P05000ST	1 L	1	-

Standardanalyser

TEST	VÄRDE		METOD
Density vid 15°C	0.847	kg/l	ASTM D4052
Kinematic Viscosity vid 40°C	66.3	mm ² /s	ASTM D445
Kinematic Viscosity vid 100°C	11.3	mm ² /s	ASTM D445
Viscosity Index	170		ASTM 2270
Flashpoint COC	254	°C	ASTM D92
Pourpoint	-42	°C	ASTM D97

Dessa egenskaper är typiska för den nuvarande produktionen. Variationer i dessa egenskaper kan förekomma.